



SIMATIC S7-1200, ANALOG OUTPUT,
SM 1232, 2 AO, +/-10V,
14 BIT RESOLUTION, OR 0-20 mA,
13 BIT RESOLUTION,

Supply voltage

24 V DC	Yes
---------	-----

Input current

Current consumption, typ.	45 mA
---------------------------	-------

from backplane bus 5 V DC, typ.	80 mA
---------------------------------	-------

Power losses

Power loss, typ.	1.5 W
------------------	-------

Analog inputs

Number of analog inputs	0
-------------------------	---

Thermocouple (TC)

Temperature compensation

Parameterizable	No
-----------------	----

Analog outputs

Number of analog outputs	2 ; Current or voltage
--------------------------	------------------------

Output ranges, voltage

-10 to +10 V	Yes
--------------	-----

Output ranges, current

0 to 20 mA	Yes
------------	-----

Load impedance (in rated range of output)	
with voltage outputs, min.	1000 Ω
with current outputs, max.	600 Ω
Analog value creation	
Measurement principle	Differential
Integrations and conversion time/ resolution per channel	
Resolution (incl. overrange)	Voltage: 14 bits; Current : 13 bits
Integration time, parameterizable	Yes
Interference voltage suppression for interference frequency f1 in Hz	40 dB, DC to 60 V for interference frequency 50 / 60 Hz
Errors/accuracies	
Temperature error (relative to output area)	25 °C $\pm 0.3\%$ to 55 °C $\pm 0.6\%$ total measurement range
Basic error limit (operational limit at 25 °C)	
Voltage, relative to output area	+/- 0,3 %
Current, relative to output area	+/- 0,3 %
Interference voltage suppression for $f = n \times (f1 \pm 1\%)$, f1 = interference frequency	
common mode voltage, max.	12 V
Interrupts/diagnostics/status information	
Alarms	
Alarms	Yes
Diagnostic alarm	Yes
Diagnostic messages	
Diagnostic functions	Yes
Monitoring the supply voltage	Yes
Wire break	Yes
Short circuit	Yes
Diagnostics indication LED	
For status of the outputs	Yes
for maintenance	Yes
Degree and class of protection	
IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
C-TICK	Yes
FM approval	Yes
Climatic and mechanical conditions for storage and transport	
Climatic conditions for storage and transport	
Free fall	

Drop height, max. (in packaging)	0.3 m ; five times, in dispatch package
Temperature	
Permissible temperature range	-40 °C to +70 °C
Air pressure acc. to IEC 60068-2-13	
Permissible air pressure	1080 to 660 hPa
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Permissible temperature range	0 °C to 55 °C horizontal installation 0 °C to 45 °C vertical installation
Air pressure acc. to IEC 60068-2-13	
Permissible air pressure	1080 to 795 hPa
Pollutant concentrations	
SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
Connection method	
required front connector	Yes
Mechanics/material	
Type of housing (front)	
Plastic	Yes
Dimensions	
Width	45 mm
Height	100 mm
Depth	75 mm
Weight	
Weight, approx.	180 g
Status	Feb 11, 2013